



MULTI PURPOSE EP

Multi purpose grease Lithium EP.

APPLICATIONS

Industrial

Automotive

Transportation

- **MULTI PURPOSE EP** is formulated for lubricating of loaded slide-,ball-, and roller-bearings, wheel -bearings, joints, chassis, and various shock loaded or vibrating applications in transport, agriculture and off road equipment, operating in wet, dusty and/or dry conditions.
- **MULTI PURPOSE EP** is suitable apply to lubrication for industrial machines, equipments requiring a NLGI 2/3 grade.
- **MULTI PURPOSE EP** is a truly Extreme Pressure grease.

SPECIFICATIONS

International specifications

- DIN 51502 KP2/3K-20
- ISO 6743-9: L-XBCDB 2/3

ADVANTAGES

- Forming a durable lubrication film, resulting in protection to metal surface
- Anti vibration and high load.
- Excellent mechanical stability avoiding ejection or loss of consistency during operation.
- Excellent adhesion and preventing lost oil by high dropping point
- Good thermal stability, resistance to temperature variations.

CHARACTERISTICS	METHOD	EP 2 /3
Soap/thickener		Lithium
Color		Yellowish brown
NLGI grade	D-217	260 /240
Dropping point, °C	D-2265	180 /190
Kinematic V. of the base oil at 40°C, mm ² /s (cSt)	D-445	150
Operating temperature range, °C		-20 to 120
Timken OK load, lbs	D-2509	45
Rust	D-1743	Pass

Above characteristics are indicative typical values